

ASTRA ES SOFT TOUCH A-7 (RUBBER EFFECT)

MATERIAL SAFETY DATA SHEET

Hazardous according to criteria of Worksafe Australia

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

CODE: 0024020
PRODUCT NAME ES SOFT TOUCH A-7 (RUBBER EFFECT)

1.2 USE OF THE SUBSTANCE / PREPARATION

1.3 COMPANY IDENTIFICATION

Name ASTRA PAINTS (AUST) PTY LTD
Full address 280 Wolseley Place, Thomastown 3074
District and Country Victoria, Australia
Tel. 03 9469 5711 Fax 03 9469 5722

1.4 EMERGENCY TELEPHONE

For urgent inquiries refer to 280 Wolseley Place, Thomastown 3074.

2. COMPOSITION / INFORMATION ON INGREDIENTS

Contains:

XYLENE	25,5 <= C < 27	R10
CAS NO 1330-20-7		XN R20/21
CE NO 215-535-7		XI R38
INDEX NO 601-022-00-9		
N-BUTYL ACETATE	25,5 <= C < 27	R10
CAS NO 123-86-4		R66
CE NO 204-658-1		R67
INDEX NO 607-025-00-1		
2-BUTYNE-1,4-DIOL	0,5 <= C < 0,6	T R23/25
CAS NO 110-65-6		C R34
CE NO 203-788-6		XN R21
INDEX NO 603-076-00-9		XN R48/22
		XI R43

The complete text of -R- phrases is specified in section 16.

3. HAZARDS IDENTIFICATION

3.1 SUBSTANCE/PREPARATION CLASSIFICATION

This preparate is dangerous under 67/548/EEC and 1999/45/EC regulations and subsequent amendments. Therefore, this preparate requires a safety data sheet according to the 91/155/EC regulation and subsequent amendments. Further information on health and/or environmental hazards can be found in sections 11 and 12 of this sheet

Danger Symbols: Xn
Phrases R: 10-20/21-38-66

3.2 DANGER IDENTIFICATION

Because of its chemical-physical features, this product is graded as flammable (flash-point ≥ 21 °C or higher and ≤ 55 °C or lower).

HARMFUL BY INHALATION AND IN CONTACT WITH SKIN.

IRRITATING TO SKIN.

REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING.

This product contains sensitizing substance/s and may cause allergic reactions.

4. FIRST AID MEASURES

EYES:

Irrigate copiously with clean, fresh water for at least 15 minutes.

Seek medical advice.

SKIN

Immediately wash with plenty of water. Remove all contaminated clothing. Obtain immediate medical attention. Wash contaminated clothing separately before using them again.

INHALATION

Remove to open air. If breathing is irregular or stopped, administer artificial respiration. Obtain immediate medical attention.

INGESTION

Obtain immediate medical attention. Induce vomiting only if indicated by the doctor. Give nothing by mouth to an unconscious person.

5. FIRE-FIGHTING MEASURES

Closed containers exposed to the heat of a fire may lead to pressure rise and explode. For information on environmental and health risks, protection of the respiratory airways, ventilation and individual protective measures, refer to the other sections of this sheet.

Extinguishing measures: CO₂, foam, chemical powder for flammable liquids. Water may not be effective to extinguish the fire, nevertheless it should be used to cool the containers exposed to flames and prevent fires and explosions. For leakage and spillage that have not caught fire, nebulized water may be used to disperse the flammable vapours and protect the people involved in stopping the leakage.

Equipment: wear equipment complete with helmet and face shield and protection of the neck, selfbreathing apparatus at pressure or demand, insulative jacket and trousers, with bands around the arms, legs and waist.

6. ACCIDENTAL RELEASE MEASURES

Closed containers exposed to the heat of a fire may lead to pressure rise and explode. For information on environmental and health risks, protection of the respiratory airways, ventilation and individual protective measures, refer to the other sections of this sheet.

Extinguishing measures: CO₂, foam, chemical powder for flammable liquids. Water may not be effective to extinguish the fire, nevertheless it should be used to cool the containers exposed to flames and prevent fires and explosions. For leakage and spillage that have not caught fire, nebulized water may be used to disperse the flammable vapours and protect the people involved in stopping the leakage.

Equipment: wear equipment complete with helmet and face shield and protection of the neck, selfbreathing apparatus at pressure or demand, insulative jacket and trousers, with bands around the arms, legs and waist.

7. HANDLING AND STORAGE

Store in a well ventilated place, keeping the containers closed when not used. Do not smoke while handling. Keep far away from sources of heat, naked flames and sparks and other sources of ignition.

8. EXPOSURE CONTROL / PERSONAL PROTECTION.

XYLENE				
- TLV TWA	434	mg/m3	ACGIH	
- TLV STEL	651	mg/m3	ACGIH	
- OEL	221	mg/m3	EU (8h)	skin
N-BUTYL ACETATE				
- TLV TWA	713	mg/m3	ACGIH	
- TLV STEL	950	mg/m3	ACGIH	

In order to minimize exposure as far as possible, it is strongly recommended to use adequate individual protective measures, such as: masks suitable for the product, goggles, gloves and overall. Do not eat, drink or smoke while handling it. Accurately wash the hands with soap and water before meals and at the end of the work shift.

9. PHYSICAL AND CHEMICAL PROPERTIES

Colour:	Amber coloured
Odour:	Of the various solvents
Physical Appearance	High viscosity liquid
Solubility:	Immiscible
Viscosity	N.A.
Vapour density:	N.A.
Evaporation speed:	N.A.
Comburent properties:	No
Partition coefficient (n-octanol/water)	N.A.
Specific Weight (KGs./dm ³):	0,97
Solid Content % (±1):	46,2
VOC % (Volatile Organic Compounds) (±1):	53,8
pH	N.A.
Boiling point	N.A.
Flash point	>21°C
Explosive properties	N.A.
Vapour pressure	N.A.
Specific gravity	0,970Kg/l

10. STABILITY AND REACTIVITY

The product is stable in normal conditions of use and storage. When heated or in the event of a fire, carbonoxides may be released and vapours which are dangerous to health. The vapours may also form explosive mixtures with the air.

The xylene present is stable but may give violent reactions if placed in contact with strong oxidants such as nitric acid, sulfuric acid, perchlorates and similar agents. It is biodegradable in water and decomposes in the sunlight (photodegradable).

Nbutyl acetate easily decomposes with water especially when heated.

11. TOXICOLOGICAL INFORMATION

Acute effects: inhalation or cutaneous absorption of this product are harmful. This product may irritate mucosae, the upper respiratory tract, and eyes. Exposure symptoms may include: stinging and irritated eyes, mouth, nose, throat; cough, respiratory disorders, dizziness, headache, nausea and sickness.

In the most serious cases, inhalation of this product may cause larynx and bronchial tube edema and irritation, chemical pneumonia and pulmonary edema. Upon contact with skin, this product may irritate it, causing an increase in skin temperature, swelling and itchiness. Ingestion of even small amounts of this product may cause health problems (stomach pain, nausea, sickness, diarrhoea).

This product may have a degreasing action on the skin, producing dryness and chapped skin after repeated exposure.

Xylene: has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

N-butyl acetate: the vapours are particularly irritating to the eyes and respiratory airways and at high concentrations they are also narcotic. Frequent contact with the skin may cause dermatitis (INR nr. 31, 1987).

12. ECOLOGICAL INFORMATION

Use this product according to good working practices. Avoid litter. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation.

13. DISPOSAL CONSIDERATION

Consider the possibility of burning the product in a suitable incinerator. Acid or basic products must always be neutralized before undergoing any treatment, including biological treatment whenever feasible. If the waste is solid, it can be disposed of in a landfill..

14. TRANSPORT INFORMATION

These goods must be transported by vehicles authorized to the carriage of dangerous goods according to the provisions set out in the current edition of the Code of International Carriage of Dangerous Goods by Road (ADR) and in all the applicable national regulations.

These goods must be packed in their original packagings or in packagings made of materials resistant to their content and not reacting dangerously with it. People loading and unloading dangerous goods must be trained on all the risks deriving from these substances and on all actions that must be taken in case of emergency situations.

ROAD AND RAIL TRANSPORT:


ADR:	3
UN:	1263
Packing Group:	III
Label:	3
Nr. Kemler:	30
Proper Shipping Name:	Pitture o materie simili alle pitture
Special Provision:	640E

CARRIAGE BY SEA (SHIPPING):

IMO class:	3
UN:	1263
Packing Group:	III
Label:	3
EMS:	F-E, S-E
Proper Shipping Name:	Paint or paint related material

TRANSPORT BY AIR:	
IATA:	3
UN:	1263
Packing Group:	III
Label:	3
Cargo:	
Packaging instructions:	310
Maximum quantity:	220 L
Pass.:	
Packaging instructions:	309
Maximum quantity:	60 L

15. REGULATORY INFORMATION

Xn

HARMFUL


R10	FLAMMABLE.
R20/21	HARMFUL BY INHALATION AND IN CONTACT WITH SKIN.
R38	IRRITATING TO SKIN.
R66	REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING.
S 9	KEEP CONTAINER IN A WELL-VENTILATED PLACE.
S13	KEEP AWAY FROM FOOD, DRINK AND ANIMAL FEEDINGSTUFFS.
S23	DO NOT BREATHE GAS/FUMES/VAPOUR/SPRAY.
S36/37	WEAR SUITABLE PROTECTIVE CLOTHING AND GLOVES.
S51	USE ONLY IN WELL-VENTILATED AREAS.

Contains:
XYLENE

Contains:
2-BUTYNE-1,4-DIOL
May cause allergic reactions.

Danger labelling under regulations 67/548/EEC and 1999/45/EC and following amendments and adjustments.

Workers exposed to this chemical agent must undergo health checks according to regulation 98/24/EC.



16. OTHER INFORMATION

Text of -R- phrases quoted in section 2 of the sheet.

R10	FLAMMABLE.
R20/21	HARMFUL BY INHALATION AND IN CONTACT WITH SKIN.
R21	HARMFUL IN CONTACT WITH SKIN.
R23/25	TOXIC BY INHALATION AND IF SWALLOWED.
R34	CAUSES BURNS.
R38	IRRITATING TO SKIN.
R43	MAY CAUSE SENSITIZATION BY SKIN CONTACT.
R48/22	HARMFUL: DANGER OF SERIOUS DAMAGE TO HEALTH BY PROLONGED EXPOSURE IF SWALLOWED.
R66	REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING.
R67	VAPOURS MAY CAUSE DROWSINESS AND DIZZINESS.

GENERAL BIBLIOGRAPHY

1. Regulation 1999/45/CE and following amendments;
2. Regulation 67/548/CEE and following amendments and adjustments (technical adjustment XXIX);
3. Regulation 91/155/CEE and following amendments;
4. The Merck Index. - 10th Edition;
5. Handling Chemical Safety;
6. Niosh - Registry of Toxic Effects of Chemical Substances;
7. INRS - Fiche Toxicologique (toxicological sheet);
8. Patty - Industrial Hygiene and Toxicology;
9. N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition;

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product .

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Changes to previous review

The following sections were modified:

01 / 09

