

ASTRA COLORBRUSH TRASPARENTE

MATERIAL SAFETY DATA SHEET

Hazardous according to criteria of Worksafe Australia

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

CODE: 0024419
PRODUCT NAME: COLORBRUSH TRASPARENTE

1.2 USE OF THE SUBSTANCE / PREPARATION

1.3 COMPANY IDENTIFICATION

Name: ASTRA PAINTS (AUST) PTY LTD
Full address: 280 Wolseley Place, Thomastown 3074
District and Country: Victoria, Australia
Tel. 03 9469 5711 Fax 03 9469 5722

1.4 EMERGENCY TELEPHONE

For urgent inquiries refer to: 280 Wolseley Place, Thomastown 3074.

2. COMPOSITION / INFORMATION ON INGREDIENTS

Contains:		CONCENTRATION C	CLASSIFICATION
NAME			
XYLENE		62 <= C < 66	R10
Cas No	1330-20-7		Xn R20/21
CE No	215-535-7		Xi R38
Index No	601-022-00-9		
SEC-BUTYL ACETATE		1 <= C < 1,5	R66
Cas No	105-46-4		F R11
CE No	203-300-1		
Index No	607-026-00-7		
SOLVENT NAPHTA (PETROLEUM), MEDIUM		19,5 <= C < 21	Xn R65
Cas No	64742-88-7		
CE No	265-191-7		
Index No	649-405-00-X		

The complete text of -R- phrases is specified in section 16.

3. HAZARDS IDENTIFICATION

3.1 Substance/Preparation Classification

This preparate is dangerous under 67/548/EEC and 1999/45/EC regulations and subsequent amendments. Therefore, this preparate requires a safety data sheet according to the 91/155/EC regulation and subsequent amendments. Further information on health and/or environmental hazards can be found in sections 11 and 12 of this sheet.

Danger Symbols: Xn
Phrases R: 10-20/21-38-65

3.2 DANGER IDENTIFICATION

Because of its chemical-physical features, this product is graded as flammable (flash-point ≥ 21 °C or higher and ≤ 55 °C or lower).

HARMFUL BY INHALATION AND IN CONTACT WITH SKIN.

IRRITATING TO SKIN.

HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.

4. FIRST AID MEASURES

EYES:

Irrigate copiously with clean, fresh water for at least 15 minutes. Seek medical advice.

SKIN

Wash immediately with plenty of water. Remove contaminated clothing. If irritation persists, seek medical attention. Wash contaminated clothing before using them again.

INHALATION

Remove to open air. If breathing is irregular, seek medical advice.

INGESTION

Obtain immediate medical attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person.

5. FIRE-FIGHTING MEASURES

Closed containers exposed to the heat of a fire may lead to pressure rise and explode. For information on environmental and health risks, protection of the respiratory airways, ventilation and individual protective measures, refer to the other sections of this sheet.

Extinguishing measures: CO₂, foam, chemical powder for flammable liquids. Water may not be effective to extinguish the fire, nevertheless it should be used to cool the containers exposed to flames and prevent fires and explosions. For leakage and spillage that have not caught fire, nebulized water may be used to disperse the flammable vapours and protect the people involved in stopping the leakage.

Equipment: wear equipment complete with helmet and face shield and protection of the neck, selfbreathing apparatus at pressure or demand, insulative jacket and trousers, with bands around the arms, legs and waist.

6. ACCIDENTAL RELEASE MEASURES

Exclude sources of ignition. Cover with inert absorbent material. Collect spillages by means of sparkproof equipment. Use water only to remove residuals, so as not to run the risk of entering the sewer.

Do not let the product dry. Contaminated clothes must be left to soak in water before washing. In order to choose safety measures and protection equipment, please see the other sections of this sheet.

Spillage in waters: remove the liquid from the surface with flameproof pumps or manual pumps or suitable absorbent material. Resort to sinking and/or dispersion of the product with suitable substances in open waters, if permitted by the law.

7. HANDLING AND STORAGE

Store in a well ventilated place, keeping the containers closed when not used. Do not smoke while handling. Keep far away from sources of heat, naked flames and sparks and other sources of ignition.

8. EXPOSURE CONTROL / PERSONAL PROTECTION.

XYLENE				
- TLV TWA	434	mg/m3	ACGIH	
- TLV STEL	651	mg/m3	ACGIH	
- OEL	221	mg/m3	EU (8h)	skin
SEC-BUTYL ACETATE				
- TLV TWA	950	mg/m3	ACGIH	

In order to minimize exposure as far as possible, it is strongly recommended to use adequate individual protective measures, such as: masks suitable for the product, goggles, gloves and overall. Do not eat, drink or smoke while handling it. Accurately wash the hands with soap and water before meals and at the end of the work shift.

9. PHYSICAL AND CHEMICAL PROPERTIES

Colour:	Amber coloured
Odour:	Of the various solvents
Physical Appearance	Liquid
Solubility:	Immiscible
Viscosity	N.A.
Vapour density:	N.A.
Evaporation speed:	N.A.
Comburent properties:	No
Partition coefficient (n-octanol/water)	N.A.
Specific Weight (KGs./dm ³):	0,87
Solid Content % (±1):	15,9
VOC % (Volatile Organic Compounds) (±1):	84,1
pH	N.A.
Boiling point	N.A.
Flash point	>21°C
Explosive properties	N.A.
Vapour pressure	N.A.
Specific gravity	0,870Kg/l

10. STABILITY AND REACTIVITY

The product is stable in normal conditions of use and storage. When heated or in the event of a fire, carbonoxides may be released and vapours which are dangerous to health. The vapours may also form explosive mixtures with the air.

The xylene present is stable but may give violent reactions if placed in contact with strong oxidants such as nitric acid, sulfuric acid, perchlorates and similar agents. It is biodegradable in water and decomposes in the sunlight (photodegradable).

11. TOXICOLOGICAL INFORMATION

Acute effects: inhalation or cutaneous absorption of this product are harmful. This product may irritate mucosae, the upper respiratory tract, and eyes. Exposure symptoms may include: stinging and irritated eyes, mouth, nose, throat; cough, respiratory disorders, dizziness, headache, nausea and sickness.

In the most serious cases, inhalation of this product may cause larynx and bronchial tube edema and irritation, chemical pneumonia and pulmonary edema. Upon contact with skin, this product may irritate it, causing an increase in skin temperature, swelling and itchiness. Ingestion of even small amounts of this product may cause health problems (stomach pain, nausea, sickness, diarrhoea).

The introduction of even small quantities of this liquid into the respiratory system in case of ingestion or vomit may cause bronchopneumonia and pulmonary edema.

Xylene: has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

12. ECOLOGICAL INFORMATION

Use this product according to good working practices. Avoid litter. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation.

Non-aromatic mineral white spirits tends to be distributed exclusively in the air where it is photodegradable. The small amount that remains in the water tends to deposit at the bottom and is biodegraded; it is thus not bioaccumulated by fish. In the soil the substance remains absorbed and is unable to reach the subterranean layers.

13. DISPOSAL CONSIDERATION

Consider the possibility of burning the product in a suitable incinerator. Acid or basic products must always be neutralized before undergoing any treatment, including biological treatment whenever feasible. If the waste is solid, it can be disposed of in a landfill.

14. TRANSPORT INFORMATION

These goods must be transported by vehicles authorized to the carriage of dangerous goods according to the provisions set out in the current edition of the Code of International Carriage of Dangerous Goods by Road (ADR) and in all the applicable national regulations.

These goods must be packed in their original packagings or in packagings made of materials resistant to their content and not reacting dangerously with it. People loading and unloading dangerous goods must be trained on all the risks deriving from these substances and on all actions that must be taken in case of emergency situations.

ROAD AND RAIL TRANSPORT:

ADR:	3
UN:	1263
Packing Group:	III
Label:	3
Nr. Kemler:	30
Proper Shipping Name:	Pitture o materie simili alle pitture
Special Provision:	640E

CARRIAGE BY SEA (SHIPPING):

IMO class:	3
UN:	1263
Packing Group:	III
Label:	3
EMS:	F-E, S-E
Marine Pollutant	
Proper Shipping Name:	Paint or paint related material

TRANSPORT BY AIR:

IATA:	3
UN:	1263
Packing Group:	III
Label:	3
Cargo:	
Packaging instructions:	310
Maximum quantity:	220 L
Pass.:	
Packaging instructions:	309
Maximum quantity:	60 L

15. REGULATORY INFORMATION



R10	FLAMMABLE.
R20/21	HARMFUL BY INHALATION AND IN CONTACT WITH SKIN.
R38	IRRITATING TO SKIN.
R65	HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.
S13	KEEP AWAY FROM FOOD, DRINK AND ANIMAL FEEDINGSTUFFS.
S23	DO NOT BREATHE GAS/FUMES/VAPOUR/SPRAY.
S36/37	WEAR SUITABLE PROTECTIVE CLOTHING AND GLOVES.
S51	USE ONLY IN WELL-VENTILATED AREAS.
S62	IF SWALLOWED, DO NOT INDUCE VOMITING: SEEK MEDICAL ADVICE IMMEDIATELY AND SHOW THIS CONTAINER OR LABEL.

CONTAINS:

XYLENE
SOLVENT NAPHTA (PETROLEUM), MEDIUM

Danger labelling under regulations 67/548/EEC and 1999/45/EC and following amendments and adjustments.

Workers exposed to this chemical agent must undergo health checks according to regulation 98/24/EC.

16. OTHER INFORMATION

Text of -R- phrases quoted in section 2 of the sheet.

R10	FLAMMABLE.
R11	HIGHLY FLAMMABLE.
R20/21	HARMFUL BY INHALATION AND IN CONTACT WITH SKIN.
R38	IRRITATING TO SKIN.
R65	HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.
R66	REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING.

GENERAL BIBLIOGRAPHY

1. Regulation 1999/45/CE and following amendments;
2. Regulation 67/548/CEE and following amendments and adjustments (technical adjustment XXIX);
3. Regulation 91/155/CEE and following amendments;
4. The Merck Index. - 10th Edition;
5. Handling Chemical Safety;
6. Niosh - Registry of Toxic Effects of Chemical Substances;
7. INRS - Fiche Toxicologique (toxicological sheet);
8. Patty - Industrial Hygiene and Toxicology;
9. N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition;

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product .

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

